

SAFETY DATA SHEET**Jet A-1**

The safety data sheet is in accordance with Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

SECTION 1: Identification of the substance / mixture and of the company / undertaking

| | |
|---------------|------------|
| Date issued | 10.01.2017 |
| Revision date | 28.01.2020 |

1.1. Product identifier

| | |
|---------------------------------------------|----------------------------------------------|
| Product name | Jet A-1 |
| Extended SDS with ES incorporated, comments | Exposure Scenario available. See section 16. |

1.2. Relevant identified uses of the substance or mixture and uses advised against

| | |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Product group | Fuel. |
| Use of the substance / preparation | Fuel for aviation turbine engines fitted to aircraft. |
| Uses advised against | This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier. |

1.3. Details of the supplier of the safety data sheet

| | |
|------------------|------------------------------------------------------|
| Company name | Aviation Fuelling Services Norway AS |
| Office address | Drammensveien 134 |
| Postal address | Postboks 1154 Sentrum |
| Postcode | NO-0107 |
| City | Oslo |
| Country | Norway |
| Telephone number | +47 22 54 00 50 |
| Email | support@afsn.no |
| Website | www.afsn.no |
| Enterprise No. | 914 948 681 |

1.4. Emergency telephone number

| | |
|---------------------|---------------------------------------------------------------------------------------|
| Emergency telephone | Telephone number: +47 22 59 13 00 Description: Norwegian Poison Information Center |
|---------------------|---------------------------------------------------------------------------------------|

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP / GHS]

Flam. Liq. 3; H226
 Asp. Tox. 1; H304
 Skin Irrit. 2; H315
 STOT SE 3; H336
 Aquatic Chronic 2; H411

Substance / mixture hazardous properties

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictograms (CLP)



Composition on the label

Kerosine (petroleum), Kerosine (petroleum), hydrodesulfurized, Kerosine (Fischer-Tropsch), Full range, C8-C16 branched and linear

Signal word

Danger

Hazard statements

H226 Flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe dust / fume / gas / mist / vapours / spray.
 P280 Wear protective gloves / protective clothing / eye protection / face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.
 P331 Do NOT induce vomiting.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

2.3. Other hazards

PBT / vPvB

The substances do not meet current criteria for vPvB or PBT (very persistent and very bioaccumulative or Persistent, Bioaccumulative and Toxic).

Physicochemical effects

Static accumulator: This product may accumulate static electricity. The vapours are heavier than air and will spread along the floor. Can form explosive gas-air mixtures.

| | |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Health effect | Parts of the chemical might be absorbed through the skin. If, by vomiting, the chemical reaches the lungs, life-threatening chemical pneumonia may develop. |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|

SECTION 3: Composition / information on ingredients

3.2. Mixtures

| Substance | Identification | Classification | Contents | Notes |
|-------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|-----------|-------|
| Kerosine (petroleum) | CAS No.: 8008-20-6 EC No.: 232-366-4 REACH Reg. No.: 01-2119485517-27 | Flam. Liq. 3; H226 Skin Irrit. 2; H315 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Chronic 2; H411 | 0 - 100 % | |
| Kerosine (petroleum) , hydrodesulfurized | CAS No.: 64742-81-0 EC No.: 265-184-9 REACH Reg. No.: 01-2119462828-25 | Flam. Liq. 3; H226 Skin Irrit. 2; H315 Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Chronic 2; H411 | 0 - 100 % | |
| Kerosine (Fischer- Tropsch) , Full range, C8-C16 branched and linear | CAS No.: 848301-66-6 REACH Reg. No.: 01-0000020121-90 | Flam. Liq. 3; H226 Asp. Tox. 1; H304 | 0 - 50 % | |
| Description of the mixture | Complex mixture of hydrocarbons consisting of paraffins, cycloparaffins, aromatic and olefinic hydrocarbons with carbon numbers predominantly in the C9 to C16 range. (including xylene, trimethylbenzenes, naphthalene, cumene og ethylbenzene). Small amounts of hydrogen sulfide can be present in both vapor and liquid. May also contain several additives at <0.1% v/v each. | | | |
| Substance comments | See section 16 for explanation of hazard statements (H) listed above. | | | |

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General | Emergency telephone number: see section 1.4. In case of unconsciousness or severe accidents, call 113. |
| Inhalation | Provide rest, warmth and fresh air. Get medical attention if any discomfort continues. In case of unconsciousness, loosen tight-fitting clothing. If respiratory problems, provide artificial respiration or oxygen. Seek medical advice. |
| Skin contact | Remove contaminated clothing. Immediately flush with large amount of water, at least for 15 min. Wash skin thoroughly with soap and water. Contact physician if irritation persists. |
| Eye contact | Promptly rinse eyes with plenty of water (tempered at 20-30°C) for at least 15 minutes. Remove contact lenses and open eyes wide apart. Get medical attention if any discomfort continues. |
| Ingestion | Rinse mouth thoroughly. Do NOT induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention immediately! |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General symptoms and effects | Risk of chemical pneumonia (pneumonitis) if aspirated during and after ingestion. |
| Acute symptoms and effects | <p>Inhalation: Vapours may cause drowsiness and dizziness. In high concentrations, vapors have narcotic effect and may cause headache, fatigue, dizziness and nausea.</p> <p>The chemical may contain small amounts of hydrogen sulphide which, when exposed to severe exposure (inhalation), can cause cellular asphyxia, rhinitis, bronchitis and occasional pulmonary edema.</p> <p>Skin contact: The chemical irritates the skin and can cause itching, burning and redness. Parts of the chemical might be absorbed through the skin.</p> <p>Eye contact: May cause eye irritation. Symptoms may be stinging pain and redness in the eyes.</p> <p>Ingestion: Symptoms such as coughing, breathing difficulties, vomiting or lethargy may indicate chemical pneumonitis.</p> |

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|----------------------------------------|-----------------------------------------------------------------------|
| Medical monitoring for delayed effects | Chemical pneumonia. |
| Other information | Treat symptomatically. No specific information from the manufacturer. |

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable extinguishing media | In case of major fire and large quantities: Foam. Water spray, fog or mist. Small fires: Powder. Carbon dioxide (CO ₂). Sand. Earth. |
| Improper extinguishing media | Do not use water jet. Avoid using foam and water on the same surface at the same time as the water will destroy the foam. |

5.2. Special hazards arising from the substance or mixture

| | |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fire and explosion hazards | Flammable liquid and vapour. Closed containers can burst violently when heated, due to excess pressure build-up. Can form explosive gas-air mixtures. Vapours are heavier than air and may spread near ground to sources of ignition. Static accumulator: This product may accumulate static electricity. |
| Hazardous combustion products | May include, but is not limited to: Carbon dioxide (CO ₂). Carbon monoxide (CO). Sulfur oxides. Unspecified organic compounds. |

5.3. Advice for firefighters

| | |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal protective equipment | Use compressed air equipment when the chemical is involved in fire. In case of evacuation, an approved protection mask should be used. See also section 8. |
| Other information | If there is no risk involved, move the containers to a safe place. If not possible, cool with water from a safe position. Extinguishing water must not be discharged into drains. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| General measures | Keep away from sources of ignition - No smoking. |
| Personal protection measures | Provide adequate ventilation. Use protective equipment as referred to in section 8. Avoid inhalation of vapours and contact with skin and eyes. |

6.2. Environmental precautions

| | |
|--------------------------------------|---------------------------------------------------------|
| Environmental precautionary measures | Do not allow to enter into sewer, water system or soil. |
|--------------------------------------|---------------------------------------------------------|

6.3. Methods and material for containment and cleaning up

| | |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Clean up | Shut off leaks if without risk. Collect with absorbent, non-combustible material into suitable containers. Proposals for inert materials: sand, kieselguhr, universal binder. Collect in a suitable container and dispose as hazardous waste according to section 13. In cases where a lot of liquid is spilled (> 1 barrel), the spill is transferred mechanically by, for example, a vacuum tank truck which transports the waste to a collection tank for recycling or safe disposal. Do not rinse material debris with water. |
| Other information | Vapours may form explosive mixtures with air on the ground. |

6.4. Reference to other sections

| | |
|--------------------|--------------------------------|
| Other instructions | See also sections 7, 8 and 13. |
|--------------------|--------------------------------|

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Handling | Provide adequate ventilation. Mechanical ventilation or local exhaust ventilation may be required. Use protective equipment as referred to in section 8. Avoid inhalation of vapours and contact with skin and eyes. Avoid swallowing. Product transfer: Wait 2 minutes after tank filling (for tanks such as those on road tanker vehicles) before opening hatches or manholes. Wait 30 minutes after tank filling (for large storage tanks) before opening hatches or manholes. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). |
|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Protective safety measures

| | |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Safety measures to prevent fire | Do not use near naked flames or glowing materials. Keep away from sources of ignition - No smoking. Do not spray on a naked flame or red-hot material. Take precautionary measures against static discharges. Ground / bond container and receiving equipment. Use explosion-proof electrical / ventilating / lighting / / equipment. Use only non-sparking tools. |
| Additional information | Vapors may form explosive mixtures with air. The vapours are heavier than air and will spread along the floor. |
| Advice on general occupational hygiene | Do not eat, drink or smoke during work. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash contaminated clothing before reuse. Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse. |

7.2. Conditions for safe storage, including any incompatibilities

| | |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Storage | Storage on barrels and in small containers: Use approved containers. Store in a well-ventilated place. Tank storage: Tanks must be specifically designed for use with this product. Bulk storage tanks should be diked (bunded). Follow rules for flammable liquids. |
| Conditions to avoid | Avoid heat, flames and other sources of ignition. |

Conditions for safe storage

| | |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Packaging compatibilities | Suitable material: For containers, or container linings use carbon steel and low alloy steel. Aluminium may also be used for applications where it does not present an unnecessary fire hazard. For container linings the following may also be used: Unplasticized polyvinyl chloride (U-PVC), Fluoropolymers (PTFE), Polyvinylidene fluoride (PVDF), Polyetheretherketone (PEEK), Polyamide (PA-11). For seals and gaskets use: Fluoroelastomer (FKM), Viton A, and Viton B, Nitrile butadiene (NBR), Buna-N. For coating (paint) materials use: High build, amine adduct-cured epoxy. Unsuitable material: For containers or container linings, examples of materials to avoid are: Polyethylene (PE, HDPE), Polypropylene (PP), Polymethyl methacrylate (PMMA), Acrylonitrile butadiene styrene (ABS). For seals and gaskets, examples of materials to avoid are: Natural rubber (NR), Ethylene Propylene (EPDM), Polychloroprene (CR) - Neoprene, Butyl (IIR), Chlorosulphonated polyethylene (CSM), e.g. Hypalon. |
| Advice on storage compatability | Keep away from: Strong oxidizing agents. Food and feed. |

7.3. Specific end use(s)

| | |
|-----------------|-----------------------------------------|
| Specific use(s) | See section 1.2. See exposure scenario. |
|-----------------|-----------------------------------------|

SECTION 8: Exposure controls / personal protection

8.1. Control parameters

| Substance | Identification | Exposure limits | TWA Year |
|--------------|-------------------|-------------------------------------------------------------------------------------------------------|----------|
| Ethylbenzene | CAS No.: 100-41-4 | Limit value (8 h) : 20 mg/m ³ Limit value (8 h) : 5 ppm Exposure limit letter | |

| | | |
|-------------------------------------------|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Xylen | CAS No.: 1330-20-7 | Letter code: H, K, E Limit value (8 h) : 25 ppm Limit value (8 h) : 108 mg/ m ³ H |
| Cumene | CAS No.: 98-82-8 | Limit value (8 h) : 20 ppm Limit value (8 h) : 100 mg/ m ³ Exposure limit letter Letter code: HK Limit value (short term) Value: 50 ppm Limit value (short term) Value: 250 mg/m ³ Exposure limit letter Letter code: S |
| Naphthalene | CAS No.: 91-20-3 | Limit value (8 h) : 10 ppm Limit value (8 h) : 50 mg/m ³ Exposure limit letter Letter code: E |
| Trimetylbenzen | CAS No.: 25551-13-7 | Limit value (8 h) : 20 ppm Limit value (8 h) : 100 mg/ m ³ Exposure limit letter Letter code: E Comments: Mesitylene (trimethylbenzenes) |
| Hydrogen sulphide | CAS No.: 7783-06-4 | Limit value (8 h) : 5 ppm Limit value (8 h) : 7 mg/m ³ Limit value (short term) Value: 10 ppm Limit value (short term) Value: 14 mg/m ³ |
| Decanes and higher aliphatic hydrocarbons | | Limit value (8 h) : 40 ppm Limit value (8 h) : 275 mg/ m ³ |

Control parameters comments

Hydrogen sulphide has notations; T for 10ppm/14 mg/m³.

Explanation of the notations:

E = The EU has adopted a recommended limit value for the substance.

H = Can be absorbed through the skin.

Carc = Capable of causing cancer and/or heritable genetic damage.

S = The short-term exposure limit: the average concentration of a chemical substance in an employee's breathing zone that must not be exceeded over a given reference period. The reference period is 15 minutes unless otherwise specified.

T = ceiling value

References (laws/regulations):

Norwegian regulation on exposure limits: FOR 2011-12-06 nr 1358 Forskrift om tiltaks- og grenseverdier (sist endret gjennom FOR-2018-12-20-2186).

8.2. Exposure controls**Precautionary measures to prevent exposure**

| | |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Technical measures to prevent exposure | <p>Provide adequate ventilation. The personal protective equipment must be CE-marked and the latest version of the standards shall be used. The protective equipment and the specified standards recommended below are only suggestions, and should be selected on advice from the supplier of such equipment.</p> <p>A risk assessment of the work place/work activities (the actual risk) may lead to other control measures. The protection equipment's suitability and durability will depend on application.</p> |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Eye / face protection

| | |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye protection equipment | <p>Description: Wear approved chemical safety goggles where eye exposure is reasonably probable.</p> <p>Reference to relevant standard: EN 166 (Personal eye-protection. Specifications).</p> |
| Additional eye protection measures | <p>Eye wash facilities should be available at the work place. Either a fixed eye wash facility connected to the drinking water (preferably warm water) or a portable disposable unit.</p> |

Hand protection

| | |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable materials | <p>Nitrile. For incidental contact/splash protection Neoprene, PVC gloves may be suitable.</p> |
| Breakthrough time | <p>Comments: Nitrilrubber: > 240 minutes</p> |
| Thickness of glove material | <p>Comments: No specific information from the manufacturer.</p> |
| Hand protection equipment | <p>Description: Use chemical resistant gloves. Glove thickness must be chosen in consultation with the glove supplier, who can inform about the breakthrough time for the glove. The gloves abilities may vary among the different glove manufacturers.</p> <p>Reference to relevant standard: BS-EN 374 (Protective gloves against chemicals and micro-organisms). BS-EN 420 (Protective gloves. General requirements and test methods).</p> |
| Additional hand protection measures | <p>Replace gloves if signs of wear and tear.</p> |

Skin protection

| | |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recommended protective clothing | <p>Description: Wear apron or protective clothing in case of contact. Bruk av antistatiske verneklær må vurderes.</p> |
| Additional skin protection measures | <p>Remove contaminated clothing and wash the skin thoroughly with soap and water after work. Wash contaminated clothing before reuse. Emergency shower should be available at the workplace.</p> |

Respiratory protection

| | |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recommended respiratory protection | <p>Description: In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with combination filter (type A/P2). At work in confined or poorly ventilated spaces, respiratory protection with air supply must be used.</p> <p>Reference to relevant standard: EN 14387 (Respiratory protective devices. Gas filter(s) and combined filter(s). Requirements, testing, marking). EN 12083 (Respiratory protective devices. Filters with breathing hoses,</p> |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

(Non-mask mounted filters). Particle filters, gas filters, and combined filters. Requirements, testing, marking).
 BS-EN 136 (Respiratory protective devices. Full face masks. Requirements, testing, marking)
 BS-EN 140 (Respiratory protective devices. Half masks and quarter masks. Requirements, testing, marking)

Appropriate environmental exposure control

| | |
|---------------------------------|---------------------------------------------------------|
| Environmental exposure controls | Do not allow to enter into sewer, water system or soil. |
|---------------------------------|---------------------------------------------------------|

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--------------------------------------------|----------------------------------------------------------------------------------------------|
| Physical state | Liquid. |
| Colour | Colourless. |
| Odour | Not specified by the manufacturer. |
| Odour limit | Comments: Not specified by the manufacturer. |
| pH | Comments: Not specified by the manufacturer. |
| Melting point / melting range | Comments: Not specified by the manufacturer. |
| Boiling point / boiling range | Value: 150 - 290 °C |
| Flash point | Value: 38 - 62 °C |
| Evaporation rate | Comments: Not specified by the manufacturer. |
| Flammability (solid, gas) | Not relevant. |
| Explosion limit | Comments: Not specified by the manufacturer. |
| Vapour pressure | Value: 1 - 3,7 kPa Temperature: 38,0 °C Value: 1,6 - 7 kPa Temperature: 50,0 °C |
| Vapour density | Comments: Not specified by the manufacturer. |
| Relative density | Comments: See density. |
| Density | Value: ~ 799 kg/m ³ Temperature: 15 °C |
| Solubility | Medium: Water Comments: Insignificant. |
| Partition coefficient: n-octanol/ water | Value: 2 - 10 |
| Spontaneous combustability | Comments: Not specified by the manufacturer. |
| Decomposition temperature | Comments: Not specified by the manufacturer. |
| Viscosity | Value: 1 - 2,5 mm ² /s Temperature: 40 °C Type: Kinematic |

| | |
|----------------------|--------------------------------------------------------------------------|
| Explosive properties | The chemical is not explosive, but may form explosive mixtures with air. |
| Oxidising properties | Not specified by the manufacturer. |

9.2. Other information

Physical hazards

| | |
|--------------|-------------------------|
| Conductivity | Comments: 50 - 600 pS/m |
|--------------|-------------------------|

Other physical and chemical properties

| | |
|----------|--------------------------------------|
| Comments | No further information is available. |
|----------|--------------------------------------|

SECTION 10: Stability and reactivity

10.1. Reactivity

| | |
|------------|-------------------------------|
| Reactivity | Oxidises on contact with air. |
|------------|-------------------------------|

10.2. Chemical stability

| | |
|-----------|-----------------------------------------------------------------|
| Stability | Stable under normal temperature conditions and recommended use. |
|-----------|-----------------------------------------------------------------|

10.3. Possibility of hazardous reactions

| | |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Possibility of hazardous reactions | Arise in contact with incompatible materials (see section 10.5) and/or under inappropriate conditions (see section 10.4). |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------|

10.4. Conditions to avoid

| | |
|---------------------|-----------------------------------------------------------------------------------|
| Conditions to avoid | Heat, sparks or open flame. Take precautionary measures against static discharge. |
|---------------------|-----------------------------------------------------------------------------------|

10.5. Incompatible materials

| | |
|--------------------|--------------------------|
| Materials to avoid | Strong oxidizing agents. |
|--------------------|--------------------------|

10.6. Hazardous decomposition products

| | |
|----------------------------------|-----------------------------------------------------|
| Hazardous decomposition products | None under normal conditions. See also section 5.2. |
|----------------------------------|-----------------------------------------------------|

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Other information regarding health hazards

| | |
|----------------------------------|-------------------------|
| Acute toxicity, mixture estimate | Dose: LD50 |
| | Route of exposure: Oral |
| | Value: > 2000 mg/kg |
| | Comments: Rat |
| | Dose: LC50 |

| | |
|----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | <p>Route of exposure: Inhalation. Value: > 5 mg/l Comments: Rat /4 hours</p> <p>Dose: LD50 Route of exposure: Dermal Value: > 2000 mg/kg Comments: Rabbit</p> |
| Assessment of acute toxicity, classification | Based on available data, the classification criteria are not met. |
| Assessment of skin corrosion / irritation, classification | Irritating to skin. |
| Assessment of eye damage or irritation, classification | Based on available data, the classification criteria are not met. |
| Assessment of respiratory sensitisation, classification | Based on available data, the classification criteria are not met. |
| Assessment of skin sensitisation, classification | Based on available data, the classification criteria are not met. |
| Assessment of germ cell mutagenicity, classification | Based on available data, the classification criteria are not met. |
| Assessment of carcinogenicity, classification | Based on available data, the classification criteria are not met. Cumene and ethylbenzene is not classified as carcinogenic, but is marked as carcinogenic in the Norwegian working exposure limit list. |
| Assessment of reproductive toxicity, classification | Based on available data, the classification criteria are not met. |
| Assessment of specific target organ toxicity - single exposure, classification | May cause drowsiness or dizziness. Classification: STOT SE 3: H336. |
| Assessment of specific target organ toxicity - repeated exposure, classification | Based on available data, the classification criteria are not met. |
| Assessment of aspiration hazard, classification | May be fatal if swallowed and enters airways. |

Symptoms of exposure

| | |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| In case of ingestion | Symptoms such as coughing, breathing difficulties, vomiting or lethargy may indicate chemical pneumonitis. |
| In case of skin contact | The chemical irritates the skin and can cause itching, burning and redness. Parts of the chemical might be absorbed through the skin. |
| In case of inhalation | <p>Vapours may cause drowsiness and dizziness. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.</p> <p>Kjemikaliet kan inneholde små mengder hydrogensulfid som ved alvorlig eksponering (innånding) kan føre til cellulær asfyksi, rihnitt, bronkitt og sporadisk lungeødem.</p> |
| In case of eye contact | May cause eye irritation. Symptoms may be stinging pain and redness in the eyes. |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Substance | Kerosine (petroleum) |
| Aquatic toxicity, fish | Value: 0,098 mg/l Effect dose concentration : NOEC Test reference: Petrotox model Comments: Source: REACH dossier information. |
| Substance | Kerosine (petroleum), hydrodesulfurized |
| Aquatic toxicity, fish | Value: 0,098 mg/l Effect dose concentration : NOEC Test reference: Petrotox model Comments: Source: REACH dossier information. |
| Substance | Kerosine (petroleum) |
| Aquatic toxicity, algae | Value: 1 - 3 mg/l Effect dose concentration : EL50 Test duration: 72 hour(s) Species: Raphidocelis subcapitata Test reference: OECD 201 Comments: Source: REACH dossier information. |
| Substance | Kerosine (petroleum), hydrodesulfurized |
| Aquatic toxicity, algae | Value: 1 - 3 mg/l Effect dose concentration : EL50 Test duration: 72 hour(s) Species: Raphidocelis subcapitata Test reference: OECD 201 Comments: Source: REACH dossier information. |
| Substance | Kerosine (petroleum) |
| Aquatic toxicity, crustacean | Value: 0,89 mg/l Effect dose concentration : EL50 Species: Daphnia magna Comments: Source: REACH dossier information. |
| Substance | Kerosine (petroleum), hydrodesulfurized |
| Aquatic toxicity, crustacean | Value: 0,89 mg/l Effect dose concentration : EL50 Species: Daphnia magna Comments: Source: REACH dossier information. |
| Ecotoxicity | Toxic to aquatic life with long lasting effects. Additional test data is available from the supplier/manufacturer. |

12.2. Persistence and degradability

| | |
|------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Persistence and degradability description/evaluation | Volatile solvents are rapidly oxidized by photochemical reaction in air. Major constituents in the chemical; Expected to be biodegradable. |
|------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|

12.3. Bioaccumulative potential

| | |
|-----------------------------|----------------------------------------------------------------------------------|
| Bioaccumulation, evaluation | The product contains potentially bioaccumulating substances. Log Pow: 2 - 10. |
|-----------------------------|----------------------------------------------------------------------------------|

12.4. Mobility in soil

| | |
|----------|------------------------------------------------------------------------------------------------------------------|
| Mobility | Evaporates within one day from water or soil surfaces. May contaminate soil and groundwater. Floats on water. |
|----------|------------------------------------------------------------------------------------------------------------------|

12.5. Results of PBT and vPvB assessment

| | |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Results of PBT and vPvB assessment | The substances do not meet current criteria for vPvB or PBT(very persistent and very bioaccumulative or Persistent, Bioaccumulative and Toxic). |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|

12.6. Other adverse effects

| | |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Additional ecological information | Do not allow to enter into sewer, water system or soil. Forms an oil film on water surfaces that may harm organisms in the water and disrupt oxygen transport in the boundary layer between air and water. |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Appropriate methods of disposal for the chemical | Disposed of as hazardous waste by approved contractor. The waste code (EWC-Code) is intended as a guide. The code must be chosen by the user, if the use differs from the one mentioned below. |
| EWC waste code | EWC waste code: 130703 other fuels (including mixtures) Classified as hazardous waste: Yes |
| NORSAS | 7023 Fuel and heating oil. |
| Other information | Do not empty into drains. |

SECTION 14: Transport information

| | |
|-----------------|-----|
| Dangerous goods | Yes |
|-----------------|-----|

14.1. UN number

| | |
|-------------|------|
| ADR/RID/ADN | 1863 |
| IMDG | 1863 |
| ICAO/IATA | 1863 |

14.2. UN proper shipping name

| | |
|------------------------------------------|--------------------------------|
| Proper shipping name English ADR/RID/ADN | FUEL, AVIATION, TURBINE ENGINE |
| ADR/RID/ADN | FUEL, AVIATION, TURBINE ENGINE |
| IMDG | FUEL, AVIATION, TURBINE ENGINE |
| ICAO/IATA | FUEL, AVIATION, TURBINE ENGINE |

14.3. Transport hazard class(es)

| | |
|---------------------------------|----|
| ADR/RID/ADN | 3 |
| Classification code ADR/RID/ADN | F1 |
| IMDG | 3 |
| ICAO/IATA | 3 |

14.4. Packing group

| | |
|-------------|-----|
| ADR/RID/ADN | III |
| IMDG | III |
| ICAO/IATA | III |

14.5. Environmental hazards

| | |
|-----------------------|-----|
| IMDG Marine pollutant | Yes |
|-----------------------|-----|

14.6. Special precautions for user

| | |
|-------------------------------------|------------------------------------|
| Special safety precautions for user | Not specified by the manufacturer. |
|-------------------------------------|------------------------------------|

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

| | |
|--------------|--------------------------------|
| Product name | FUEL, AVIATION, TURBINE ENGINE |
|--------------|--------------------------------|

Additional information

| | |
|--------------------------|---|
| Hazard label ADR/RID/ADN | 3 |
| Hazard label IMDG | 3 |
| Hazard label ICAO/IATA | 3 |

ADR/RID Other information

| | |
|--------------------------------------|-----|
| Tunnel restriction code | D/E |
| Transport category | 3 |
| Hazard No. | 30 |
| Other applicable information ADR/RID | 30 |

IMDG Other information

| | |
|-----|----------|
| EmS | F-E, S-E |
|-----|----------|

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

| | |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| References (laws/regulations) | Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP-regulation) with later amendments. Regulation (EC) No 1907/2006 on the registration, evaluation, authorization and |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|


| | |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | restriction of chemicals (REACH Regulation), with later amendments. Norwegian regulation on waste, 01.06.2004 no. 930, with later amendments. Dangerous Goods regulations |
| Declaration No. | 325758 |

15.2. Chemical safety assessment

| | |
|--------------------------------------|-----|
| Chemical safety assessment performed | Yes |
|--------------------------------------|-----|

SECTION 16: Other information

| | |
|------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| List of relevant H-phrases (Section 2 and 3) | H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H228 Flammable solid. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H330 Fatal if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer H373 May cause damage to organs through prolonged or repeated exposure H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. |
| Key literature references and sources for data | The Safety Data Sheet is based on information provided by the producer. Earlier version(s) of the safety data sheet. |
| Abbreviations and acronyms used | ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road EWC: European Waste Code (a code from the EU's common classification system for waste) EC50: The effective concentration of substance that causes 50% of the maximum response EL50: The effective concentration of substance (slightly soluble) that causes 50% of the maximum response. IATA: The International Air Transport Association ICAO: The International Civil Aviation Organisation IMDG: The International Maritime Dangerous Goods Code LC50: Median concentration lethal to 50% of a test population. LD50: Lethal dose, is the amount of a substance given to a group of test animals, which causes the death of 50%. NOEC: No observed effect concentration Log Pow: Partition coefficient: n-octanol / water OECD: Organisation for Economic Cooperation and Development. PBT: Persistent, Bioaccumulative and Toxic RID: The Regulations concerning the International Carriage of Dangerous Goods by Rail |

| | |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Information added, deleted or revised | vPvB: very Persistent and very Bioaccumulative |
| Checking quality of information | Layout changed. |
| Version | This SDS is quality controlled by Kiwa Teknologisk Institutt in Norway, certified according to the Quality Management System requirements specified in ISO 9001:2015. |
| Prepared by | 1 |
| Contents or index of annexed ES | Kiwa Teknologisk Institutt, Norway by Sissel Rogstad |
| Exposure scenario | 1 Manufacture of substance- Industrial 2 Use as an intermediate- Industrial 3 Distribution of substance- Industrial 4 Formulation & (re)packing of substances and mixtures- Industrial 5 Use as a fuel- Industrial 6 Use as a fuel- Professional 7 Use as a fuel - Consumer |
| |  ES JET A-1 EN.pdf |